12.7x99 (.50 Cal) M8 API

UDC manufactures small and medium caliber ammunition for all branches of the US Military, USSOCOM, the Civilian market and State Department approved customers.

CALIBER: .50 BMG (12.7x99mm)

CARTRIDGE: M8 Armor Piercing Incendiary

FUNCTION: Battle carry

BULLET WT. (GRAINS): 662.5gr API

BULLET EXTRACTION: Minimum of 90 Kg (200 lbs)

TIP ID: Grey

CASE: Brass

PRIMER: Boxer, 50M, Non-Corrosive ARMOR PENETRATION: 7/8" at 100

yards (2.2cm at 91m)

ARMOR PENETRATION: 7/8" at 100 yards (2.2cm at 91m)

VELOCITY: avg 2905 \pm 30 fps at 78 feet; SD \leq 36 fps

ACCURACY: Average Mean Radii Maximum: 30.5 cm @ 548 m (12 in @ 600

yds)

CHAMBER PRESSURE: avg ≤ 65 Kpsi @ 70 F

OPERATING TEMP: -54 C to 52 C (-65 F to 125 F)

PACKAGING: 120rds/M2A1, 240rds/Wood Crate, 11,520/Pallet, 40x48in.

3900 lbs/1769 kg per Pallet.



MANUFACTURED TO U.S. MILITARY

Specifications:

- MIL-DTL-3066
- MIL-STD-636
- MIL-STD-1916
- Drawing: 7670228

PRIMER SEALANT: Yes

CASE MOUTH SEALANT: Yes

HEADSTAMP: UDC manufacturer symbol and year of manufacture.









