12.7x99 (.50 cal) M33/M17 4:1

UDC located in Florida and Missouri, manufactures .50 caliber variants for commercial, government, and law enforcement customers.

CALIBER: Caliber .50 BMG (12.7x99mm)

CARTRIDGE: M33 Ball/ M17 Trace Linked

FUNCTION: Training or duty. Trace to 1460 meters

BULLET WT. (GRAINS): M33 2.8 g/660 gr FMJ BT

BULLET EXTRACTION: Minimum of 90 Kg (200 lbs.)

TIP ID: M33-None, M17-Red

CASE: Brass

PRIMER: Boxer, M50, Non-Corrosive

VELOCITY: 855 +/- 9 m/s (24 m from muzzle) @ 21 +/-2 C or 2905 +/-30

ft/s (78 ft from muzzle) @ 70 +/-2 F

ACCURACY: Average Mean Radii Maximum: 30.5 cm @ 548 m (12 in @ 600

yds)

CHAMBER PRESSURE: Maximum: 448 Mpa @ 21 C (65,000 psi @ 70 F)

OPERATING TEMP: -54 C to 52 C (-65 F to 125 F)

PACKAGING: 100rds 4:1 Linked/ M2A1, 200rds/Wood Crate, 9,600rds/

Pallet



MANUFACTURED TO U.S. MILITARY

Specifications:

- MIL-DTL-10190F/1318D
- MIL-STD-636
- MIL-STD-1916
- Drawing: 7553097
- Drawing: 7672165

PRIMER SEALANT: Yes

CASE MOUTH SEALANT: Yes

HEADSTAMP: UDC manufacturer symbol and year of manufacture.









